

TECHNICAL SPECIFICATIONS

| Feature | Unit | Minimum limit | Standard | Maximum limit |
|---------------|------------|---------------|----------|---------------|
| Grams/meter | g/sq.m | 113 | 125 | 138 |
| Width | inches | 49 | 52 | *** |
| Cutable width | inches | 47 | 50 | *** |
| Fabric Yield | m/kg | 5.25 | 6.06 | 7.09 |
| Ounces/yards | Oz/sq.yd | 3.3 | 3.7 | 4.1 |
| Fiber content | 100% RAYON | | | |

Certifications



Additional comments about technical specifications

Larger width is not considered to be out of specification.

NCM

| PFD | Off White/White | Dyed | Printed |
|------------|-----------------|------------|------------|
| 5516.11.00 | 5516.11.00 | 5516.12.00 | 5516.14.00 |

DIMENSIONAL STABILITY

| Shrinkage after washing (Hand wash - dry flat %) | Warp (%) | Weft (%) |
|--|----------|----------|
| | 12 | 8 |

Additional comments about dimensional stability

We do not recommend machine drying.
Do not leave dirty clothes together in a closed place for a long time,
Always keep separated in a cool and ventilated place.
Separate by light and dark colors. Use neutral soap. Do not twist.

WASHING INSTRUCTIONS



- hand wash




- do not bleach



- dry flat



- maximum temperature for
the iron heat 110C (230F)



- do not dryclean

Note - The symbols should appear in the following order: washing, bleaching, drying, ironing and professional dry cleaning.

Additional instructions to use with care symbols

- Do not tumble dry.
- Do not wring.
- Do not use steam during ironing.

STORAGE INSTRUCTIONS

- Do not hit the ends of the fabric (do not hit the top).
- Keep the packaging of the rolls until their end use.
- The identification of the rolls must always be kept.
- Stored textiles should not be exposed to the light. The exposure will compromise the fabric over time.
- Separate by batch.

GENERAL COMMENTS

- Neon colors have low resistance to light and washing, they should not be mixed with other colors and / or fabric in the same piece, they should be washed separately.
- Iron with protective fabric over the style, to avoid seam marks of seams and brightness during ironing.
- Remove the excess water without twisting, the style crumples easily.
- The washing mode is performed on the fabric, but after the fabric is converted into clothing, it must be evaluated (clothing appearance, use of other fabrics, use of interfacing / interlinings, etc).
- Be careful of the fabric getting in contact with abrasive surfaces, yarn may be tugged.
- Do not mix batches.
- Claims will be accepted within 15 days after receipt of the goods.
- All tests mentioned above were performed through NBR, ISO, AATCC standards and / or internal standards.
- It is essential to inform the purchase order, the intention to mix light and dark colors in the same piece.
- It is recommended to perform solidity tests before cutting if you are going to mix light and dark colors in the same piece.

Prepared by Sara Almeida: Quality / Kalimo
Approved by Murilo Garcia: Technical Manager